

EMC TEST REPORT

For

SAGE HUMAN ELECTRONICS INTERNATIONAL CO.,LTD

Bluetooth Speaker

Test Model: BM01

Additional Model No.: BM02, BM03, BM04, BM05, P01, SH06,
SH07, SH08, SH09, CNE-CBTSP5, CNE-CBTSP6, VK-3454-BK

Prepared for : SAGE HUMAN ELECTRONICS INTERNATIONAL
CO.,LTD
Address : 4F., A Building, Rongli Industrial Park, No.2 Guiyuan Rd.,
Guihua Community, Guanlan Town, Longhua New Dist.,
Shenzhen, China

Prepared by : Shenzhen LCS Compliance Testing Laboratory Ltd.
Address : 101, 601, Xingyuan Industrial Park, Gushu Community,
Xixiang Street, Bao'an District, Shenzhen, Guangdong,
China

Tel : (+86)755-82591330
Fax : (+86)755-82591332
Web : www.LCS-cert.com
Mail : webmaster@LCS-cert.com

Date of receipt of test sample : June 04, 2019
Number of tested samples : 1
Serial number : Prototype
Date of Test : June 04, 2019 ~ June 26, 2019
Date of Report : June 29, 2019




EMC TEST REPORT**ETSI EN 301 489-17 V3.1.1(2017-02) & EN 55032:2015 & EN 55035:2017**


Electromagnetic compatibility and Radio spectrum Matters (ERM); Electromagnetic Compatibility (EMC) standard for radio equipment and services

Report Reference No. : LCS190603040AEA**Date Of Issue : June 29, 2019****Testing Laboratory Name..... : Shenzhen LCS Compliance Testing Laboratory Ltd.****Address : 101, 601, Xingyuan Industrial Park, Gushu Community, Xixiang Street, Bao'an District, Shenzhen, Guangdong, China****Testing Location/ Procedure..... : Full application of Harmonised standards ☒
Partial application of Harmonised standards ☐
Other standard testing method ☐****Applicant's Name..... : SAGE HUMAN ELECTRONICS INTERNATIONAL CO.,LTD****Address..... : 4F., A Building, Rongli Industrial Park, No.2 Guiyuan Rd., Guihua Community, Guanlan Town, Longhua New Dist., Shenzhen, China****Test Specification****Standard : ETSI EN 301 489-1 V2.1.1 (2017-02)
ETSI EN 301 489-17 V3.1.1(2017-02)
EN 55032:2015
EN 55035:2017****Test Report Form No. : LCSEMC-1.0****TRF Originator : Shenzhen LCS Compliance Testing Laboratory Ltd.****Master TRF : Dated 2017-06****Shenzhen LCS Compliance Testing Laboratory Ltd. All rights reserved.**


This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen LCS Compliance Testing Laboratory Ltd. is acknowledged as copyright owner and source of the material. Shenzhen LCS Compliance Testing Laboratory Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

Test Item Description. : Bluetooth Speaker**Trade Mark : N/A****Test Model..... : BM01****Ratings..... : DC 7.4V by Li-ion battery(3000mAh)
Recharge by DC 5V****Result : Positive****Compiled by:**

Linda He / Administrators

Supervised by:

Aking Jin / Technique principal

Approved by:

Gavin Liang/ Manager

EMC -- TEST REPORT

Test Report No. : LCS190603040AEA

June 29, 2019

Date of issue

Test Model..... : BM01

EUT..... : Bluetooth Speaker

Applicant..... : SAGE HUMAN ELECTRONICS INTERNATIONAL CO.,LTDAddress..... : 4F, A Building, Rongli Industrial Park, No.2 Guiyuan Rd.,
Guihua Community, Guanlan Town, Longhua New Dist.,
Shenzhen, China

Telephone..... : /

Fax..... : /

Manufacturer..... : Huizhou Jiemeisi Technology Co.,LtdAddress..... : NO. 63, Qingtang Dashuling Humei Street, Xiaojinkou street
office, Huicheng District, Huizhou, City, Guangdong Province,
China.

Telephone..... : /

Fax..... : /

Factory..... : Huizhou Jiemeisi Technology Co.,LtdAddress..... : NO. 63, Qingtang Dashuling Humei Street, Xiaojinkou street
office, Huicheng District, Huizhou, City, Guangdong Province,
China.

Telephone..... : /

Fax..... : /

Test Result**Positive**

The test report merely corresponds to the test sample.

It is not permitted to copy extracts of these test result without the written permission of the test laboratory.

Revision History

Revision	Issue Date	Revisions	Revised By
000	June 29, 2019	Initial Issue	Gavin Liang

TABLE OF CONTENTS

Test Report Description	Page
TABLE OF CONTENTS	5
1. GENERAL INFORMATION	7
1.1. Product Description for Equipment Under Test (EUT)	7
1.2. Objective	7
1.3. Related Submittal(s)/Grant(s)	7
1.4. Test Methodology	7
1.5. Description of Test Facility	8
1.6. Support equipment List	8
1.7. External I/O	8
1.8. Measurement Uncertainty	8
1.9. Description Of Test Modes	9
2. SUMMARY OF TEST RESULTS	10
3. LINE CONDUCTED EMISSION	11
3.1. Conducted Emission Limit	11
3.2. Test Configuration	11
3.3. Test Data	12
4. RADIATED DISTURBANCE	13
4.1. Radiated Emission Limit	13
4.2. Test Configuration	13
4.3. Test Procedure	14
4.4. Test Data	16
5. HARMONIC CURRENT EMISSIONS	18
5.1. Test Configuration	18
5.2. Test Standard	18
5.3. Test Data	18
6. VOLTAGE FLUCTUATION AND FLICKER	19
6.1. Test Configuration	19
6.2. Test Standard	19
6.3. Test Data	19
7. GENERAL PERFORMANCE CRITERIA FOR IMMUNITY TEST	20
7.1. Performance criteria for Continuous phenomena applied to Transmitter (CT)	20
7.2. Performance criteria for Transient phenomena applied to Transmitter (TT)	20
7.3. Performance criteria for Continuous phenomena applied to Receiver (CR)	20
7.4. Performance criteria for Transient phenomena applied to Receiver (TR)	20
8. RF ELECTROMAGNETIC FIELD (80 MHZ–6000 MHZ)	22
8.1. Test Configuration	22
8.2. Test Standard	23
8.3. Severity Level	23
8.4. Test Procedure	23
8.5. Test Result	24
9. ELECTROSTATIC DISCHARGE	25
9.1. Test Configuration	25
9.2. Test Procedure	26
9.3. Test Data	26
10. ELECTRICAL FAST TRANSIENT IMMUNITY	28
10.1. Test Configuration	28
10.2. Test Standard	28

10.3. Test Procedure.....	29
10.4. Test Data	29
11. RF COMMON MODE	31
11.1. Test Configuration.....	31
11.2. Test Standard	31
11.3. Test Procedure.....	32
11.4. Test Data.....	32
12. SURGES, LINE TO LINE AND LINE TO GROUND	34
12.1. Test Configuration.....	34
12.2. Test Standard.....	34
12.3. Test Procedure.....	34
12.4. Test Data	35
13. VOLTAGE DIPS/INTERRUPTIONS IMMUNITY TEST	36
13.1. Test Configuration.....	36
13.2. Test Standard.....	36
13.3. Test Procedure.....	36
13.4. Test Data	37
14. LIST OF MEASURING EQUIPMENT	38
15.TEST SETUP PHOTOGRAPHS	40
15.1.Photo of Radiated Emissions Measurement.....	40
15.2.Photo of Power Line Conducted Emissions Measurement	41
15.3.Photo of Harmonic & Flicker Measurement	41
15.4.Photo of Electrostatic Discharge Test	42
15.5.Photo of Radio-frequency, Continuous radiated disturbance	42
15.6.Photo of Electrical Fast Transient/Burst& Surge Immunity Test	43
15.7.Photo of Injected Currents Susceptibility Test.....	43
15.8 Photo of Voltage Dips and Short Interruptions Immunity Test	44
16.EXTERNAL AND INTERNAL PHOTOS OF THE EUT	45

1. GENERAL INFORMATION

1.1. Product Description for Equipment Under Test (EUT)

EUT	: Bluetooth Speaker
Test Model	: BM01
Additional Model No.	: BM02, BM03, BM04, BM05, P01, SH06, SH07, SH08, SH09, CNE-CBTSP5, CNE-CBTSP6, VK-3454-BK
Model Declaration	: PCB board, structure and internal of these model(s) are the same, So no additional models were tested.
Power Supply	: DC 7.4V by Li-ion battery(3000mAh) Recharge by DC 5V
Hardware Version	: V2.0
Software Version	: V2.0
Bluetooth	
Frequency Range	: 2.402-2.480GHz
Channel Number	: 79 channels for Bluetooth V5.0 (DSS)
Channel Spacing	: 1MHz for Bluetooth V5.0 (DSS)
Modulation Type	: GFSK, $\pi/4$ -DQPSK for Bluetooth V5.0 (DSS)
Bluetooth Version	: V5.0
Antenna Description	: Internal Antenna, -0.58dBi (Max.)

1.2. Objective

ETSI EN 301 489-1	Electromagnetic compatibility and Radio spectrum Matters (ERM); Electro Magnetic Compatibility (EMC) standard for radio equipment and services; Part 1: Common technical requirements
ETSI EN 301 489-17	Electromagnetic compatibility and Radio spectrum Matters (ERM); Electromagnetic Compatibility (EMC) standard for radio equipment Part 17: Specific conditions for Broadband Data Transmission Systems
EN 55032	Electromagnetic compatibility of multimedia equipment—Emission Requirements
EN 55035	Electromagnetic compatibility of multimedia equipment—Immunity Requirements

The objective is to determine compliance with ETSI EN 301 489-1 V2.1.1 (2017-02) , ETSI EN 301 489-17 V3.1.1(2017-02), EN 55032:2015 and EN 55035:2017.

1.3. Related Submittal(s)/Grant(s)

No Related Submittals.

1.4. Test Methodology

All measurements contained in this report were conducted with ETSI EN 301 489-1 V2.1.1 (2017-02) , ETSI EN 301 489-17 V3.1.1(2017-02), EN 55032:2015 and EN 55035:2017.

1.5. Description of Test Facility

FCC Registration Number is 254912.
 Industry Canada Registration Number is 9642A-1.
 EMSD Registration Number is ARCB0108.
 UL Registration Number is 100571-492.
 TUV SUD Registration Number is SCN1081.
 TUV RH Registration Number is UA 50296516-001.
 NVLAP Accreditation Code is 600167-0.
 FCC Designation Number is CN5024.
 CAB identifier is CN0071.

1.6. Support equipment List

Manufacturer	Description	Model	Serial Number	Certificate
--	--	--	--	--

1.7. External I/O

I/O Port Description	Quantity	Cable
DC IN PORT	1	N/A
USB PORT	1	N/A
AUX PORT	1	N/A
TF CARD PORT	1	N/A

1.8. Measurement Uncertainty

Item	MU	Remark
Uncertainty for Power point Conducted Emissions Test	$\pm 2.42\text{dB}$	
Uncertainty for Radiation Emission test in 3m chamber (30MHz to 1GHz)	$\pm 3.54\text{dB}$	Polarize: V
	$\pm 4.1\text{dB}$	Polarize: H
Uncertainty for Radiation Emission test in 3m chamber (1GHz to 25GHz)	$\pm 2.08\text{dB}$	Polarize: H
	$\pm 2.56\text{dB}$	Polarize: V
Uncertainty for radio frequency	$\pm 3 \times 10^{-7}\text{MHz}$	
Uncertainty for conducted RF Power	$\pm 0.65\text{dB}$	
Uncertainty for temperature	$\pm 0.2^{\circ}\text{C}$	
Uncertainty for humidity	$\pm 1\%$	
Uncertainty for DC and low frequency voltages	$\pm 0.05\text{V}$	

1.9. Description Of Test Modes

There were 5 test Modes. TM1 to TM5 are shown below:

TM1: Operate in BT mode.

TM2: Operate in AUX mode.

TM3: Operate in USB mode.

TM4: SD card mode

TM5: Idle mode

***Note:

All test modes were tested, but we only recorded the worst case in this report.

2. SUMMARY OF TEST RESULTS

Rule	Description of Test Items	Result
§7.1	Reference to clauses EN 301 489-1 §8.4 AC mains power input/output ports	Compliant
§7.1	Reference to clauses EN 301 489-1 §8.3 DC power input/output ports	N/A
§7.1	Reference to clauses EN 301 489-1 §8.2 Enclosure of ancillary equipment measured on a stand alone basis	Compliant
§7.1	Reference to clauses EN 301 489-1 §8.5 Harmonic current emissions (AC mains input port)	N/A
§7.1	Reference to clauses EN 301 489-1 §8.6 Voltage fluctuations and flicker (AC mains input port)	Compliant
§7.1	Reference to clauses EN 301 489-1 §8.7 Telecommunication ports	N/A
§7.2	Reference to clauses EN 301 489-1 §9.3 Electrostatic discharge (EN 61000-4-2)	Compliant
§7.2	Reference to clauses EN 301 489-1 §9.2 Radio frequency electromagnetic field (80 MHz to 6 000 MHz)(EN 61000-4-3)	Compliant
§7.2	Reference to clauses EN 301 489-1 §9.4 Fast transients, common mode (EN 61000-4-4)	Compliant
§7.2	Reference to clauses EN 301 489-1 §9.8 Surges (EN 61000-4-5)	Compliant
§7.2	Reference to clauses EN 301 489-1 §9.5 Radio frequency, common mode (EN 61000-4-6)	Compliant
§7.2	Reference to clauses EN 301 489-1 §9.6 Transients and surges in the vehicular environment (ISO 7637-2)	N/A
§7.2	Reference to clauses EN 301 489-1 §9.7 Voltage dips and interruptions (EN 61000-4-11)	Compliant

Note: N/A means not applicable.

3. LINE CONDUCTED EMISSION

3.1. Conducted Emission Limit

ETSI EN 301 489-1 V2.1.1 (2017-02)/EN 55032


Limits for Line Conducted Emission

Frequency (MHz)	Limit (dB μ V)	
	Quasi-peak Level	Average Level
0.15~0.50	66.0 ~ 56.0 *	56.0 ~ 46.0 *
0.50~5.00	56.0	46.0
5.00~30.00	60.0	50.0

NOTE1-The lower limit shall apply at the transition frequencies.

NOTE2-The limit decreases linearly with the logarithm of the frequency in the range 0.15MHz to 0.50MHz.

3.2. Test Configuration



The setup of EUT is according with per ETSI EN 301 489-1 measurement procedure. The specification used was with the ETSI EN 301 489-1 limits.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle. The spacing between the peripherals was 10 cm.

The EUT received DC 5V charging power from the Adapter which received power through a LISN supplying power of AC 230V/50Hz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	30MHz~1000MHz
(IF)RB	9kHz


All data was recorded in the Quasi-peak and average detection mode.

Marked on both the 6 highest Quasi-Peak & 6 highest Average emissions points of the EUT.

3.3. Test Data

For pre-scan, the worst test case is TM1, and the test data was show as follow:


Model No.	BM01	Test Mode	TM1
Environmental Conditions	23.6°C, 53.9% RH	Test Engineer	Scent Hu
Pol	Line	Test Voltage	AC 230V/50Hz



	Freq	Reading	LISNFac	CabLos	Aux2Fac	Measured	Limit	Over	Remark
	MHz	dBuV	dB	dB	dB	dBuV	dBuV	dB	
1	0.16	28.34	9.59	0.02	10.00	47.95	65.34	-17.39	QP
2	0.16	9.63	9.59	0.02	10.00	29.24	55.33	-26.09	Average
3	0.19	27.20	9.62	0.02	10.00	46.84	64.20	-17.36	QP
4	0.19	6.71	9.62	0.02	10.00	26.35	54.19	-27.84	Average
5	1.35	25.22	9.63	0.05	10.00	44.90	56.00	-11.10	QP
6	1.35	9.38	9.63	0.05	10.00	29.06	46.00	-16.94	Average
7	2.13	27.52	9.64	0.05	10.00	47.21	56.00	-8.79	QP
8	2.13	9.94	9.64	0.05	10.00	29.63	46.00	-16.37	Average
9	3.53	27.69	9.65	0.06	10.00	47.40	56.00	-8.60	QP
10	3.53	14.00	9.65	0.06	10.00	33.71	46.00	-12.29	Average
11	26.42	28.98	9.71	0.13	10.00	48.82	60.00	-11.18	QP
12	26.42	10.43	9.71	0.13	10.00	30.27	50.00	-19.73	Average

Remarks: 1. Measured = Reading + LISNFac + Cable Loss + Aux2 Fac.
2. The emission levels that are 20dB below the official limit are not reported.

Model No.	BM01	Test Mode	TM1
Environmental Conditions	23.6°C, 53.9% RH	Test Engineer	Scent Hu
Pol	Neutral	Test Voltage	AC 230V/50Hz



	Freq	Reading	LISNFac	CabLos	Aux2Fac	Measured	Limit	Over	Remark
	MHz	dBuV	dB	dB	dB	dBuV	dBuV	dB	
1	0.17	20.79	9.65	0.02	10.00	40.46	64.94	-24.48	QP
2	0.17	9.95	9.65	0.02	10.00	29.62	54.94	-25.32	Average
3	0.20	19.69	9.59	0.02	10.00	39.30	63.71	-24.41	QP
4	0.20	6.91	9.59	0.02	10.00	26.52	53.71	-27.19	Average
5	1.57	24.76	9.63	0.05	10.00	44.44	56.00	-11.56	QP
6	1.57	5.70	9.63	0.05	10.00	25.38	46.00	-20.62	Average
7	2.54	25.84	9.64	0.05	10.00	45.53	56.00	-10.47	QP
8	2.54	9.93	9.64	0.05	10.00	29.62	46.00	-16.38	Average
9	5.90	24.39	9.67	0.06	10.00	44.12	60.00	-15.88	QP
10	5.90	8.22	9.67	0.06	10.00	27.95	50.00	-22.05	Average
11	26.42	24.32	9.83	0.13	10.00	44.28	60.00	-15.72	QP
12	26.42	6.35	9.83	0.13	10.00	26.31	50.00	-23.69	Average

Remarks: 1. Measured = Reading + LISNFac + Cable Loss + Aux2 Fac.
2. The emission levels that are 20dB below the official limit are not reported.

Note: For conducted emission and radiated emission test, a power supply of 230VAC and 120VAC were used for testing respectively, and only recorded the worst case of 230VAC.

4. RADIATED DISTURBANCE

4.1. Radiated Emission Limit

ETSI EN 301 489-1 V2.1.1 (2017-02)/EN 55032 Class B

Limits for radiated disturbance Below 1GHz

Frequency (MHz)	Distance (Meters)	Field Strengths Limit (dB μ V/m)
30 ~ 230	3	40
230 ~ 1000	3	47



Note: (1) The smaller limit shall apply at the combination point between two frequency bands. (2) Distance refers to the distance in meters between the measuring instrument antenna and the closed point of any part of the EUT.

Limits for radiated disturbance Above 1GHz

Frequency (MHz)	Distance (Meters)	Average Limit (dB μ V/m)	Peak Limit (dB μ V/m)
1000-3000	3	50	70
3000-6000	3	54	74

Note: The lower limit applies at the transition frequency.

4.2. Test Configuration



4.3. Test Procedure

1) Sequence of testing 30 MHz to 1 GHz

Setup:

- The equipment was set up to simulate a typical usage like described in the user manual or described by manufacturer.
- If the EUT is a tabletop system, a table with 0.8 m height is used, which is placed on the ground plane.
- If the EUT is a floor standing device, it is placed on the ground plane with insulation between both.
- Auxiliary equipment and cables were positioned to simulate normal operation conditions
- The AC power port of the EUT (if available) is connected to a power outlet below the turntable.
- The measurement distance is 3 meter.
- The EUT was set into operation.

Premeasurement:

- The turntable rotates from 0 °to 315 °using 45 °steps.
- The antenna is polarized vertical and horizontal.
- The antenna height changes from 1 to 4 meter.
- At each turntable position, antenna polarization and height the analyzer sweeps three times in peak to find the maximum of all emissions.

Final measurement:

- The final measurement will be performed with minimum the six highest peaks.
- According to the maximum antenna and turntable positions of premeasurement the software maximize the peaks by changing turntable position ($\pm 45^\circ$) and antenna movement between 1 and 4 meter.
- The final measurement will be done with QP detector with an EMI receiver.
- The final levels, frequency, measuring time, bandwidth, antenna height, antenna polarization, turntable angle, correction factor, margin to the limit and limit will be recorded. Also a plot with the graph of the premeasurement with marked maximum final measurements and the limit will be stored.

2) Sequence of testing 1 GHz to 6 GHz

Setup:

- The equipment was set up to simulate a typical usage like described in the user manual or described by manufacturer.
- If the EUT is a tabletop system, a rotatable table with 0.8 m height is used.
- If the EUT is a floor standing device, it is placed on the ground plane with insulation between both.
- Auxiliary equipment and cables were positioned to simulate normal operation conditions
- The AC power port of the EUT (if available) is connected to a power outlet below the turntable.
- The measurement distance is 3 meter.
- The EUT was set into operation.

Premeasurement:

- The turntable rotates from 0 °to 315 °using 45 °steps.
- The antenna is polarized vertical and horizontal.
- The antenna height scan range is 1 meter to 4 meter.
- At each turntable position and antenna polarization the analyzer sweeps with peak detection to find the maximum of all emissions.

Final measurement:

- The final measurement will be performed with minimum the six highest peaks.
- According to the maximum antenna and turntable positions of premeasurement the software maximize the peaks by changing turntable position ($\pm 45^\circ$) and antenna movement between 1 and 4 meter. This procedure is repeated for both antenna polarizations.
- The final measurement will be done in the position (turntable, EUT-table and antenna polarization) causing the highest emissions with Peak and Average detector.
- The final levels, frequency, measuring time, bandwidth, turntable position, EUT-table position, antenna polarization, correction factor, margin to the limit and limit will be recorded. Also a plot with the graph of the premeasurement with marked maximum final measurements and the limit will be stored.


Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	30MHz~1000MHz / RB 100kHz for QP

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency	6000 MHz
RB / VB	1MHz / 1MHz for Peak, 1 MHz / 10Hz for Average

4.4. Test Data

The worst test mode of the EUT was TM1, and its test data was showed as the follow:

Model No.	BM01	Test Mode	TM1
Environmental Conditions	23.8℃, 54.1% RH	Detector Function	Quasi-peak
Pol	Vertical	Distance	3m
Test Engineer	Scent Hu	Test Voltage	AC 230V/50Hz




Env./Ins: 23.8℃/54.1%
pol: VERTICAL

	Freq	Reading	CabLos	Antfac	Measured	Limit	Over	Remark
	MHz	dBuV	dB	dB/m	dBuV/m	dBuV/m	dB	
1	30.42	21.67	0.39	12.33	34.39	40.00	-5.61	QP
2	50.23	12.68	0.54	13.24	26.46	40.00	-13.54	QP
3	191.75	13.17	0.86	10.56	24.59	40.00	-15.41	QP
4	287.99	16.32	1.05	12.83	30.20	47.00	-16.80	QP
5	480.53	12.50	1.31	16.08	29.89	47.00	-17.11	QP
6	833.32	11.59	1.86	20.40	33.85	47.00	-13.15	QP

Note: 1. All readings are Quasi-peak values.
2. Measured= Reading + Antenna Factor + Cable Loss
3. The emission that are 20db below the official limit are not reported

Model No.	BM01	Test Mode	TM1
Environmental Conditions	23.8℃, 54.1% RH	Detector Function	Quasi-peak
Pol	Horizontal	Distance	3m
Test Engineer	Scent Hu	Test Voltage	AC 230V/50Hz



Env./Ins: 23.8℃/54.1%
pol: HORIZONTAL

	Freq	Reading	CabLos	Antfac	Measured	Limit	Over	Remark
	MHz	dBuV	dB	dB/m	dBuV/m	dBuV/m	dB	
1	49.01	10.86	0.35	13.31	24.52	40.00	-15.48	QP
2	132.22	14.62	0.76	8.77	24.15	40.00	-15.85	QP
3	191.75	21.21	0.86	10.56	32.63	40.00	-7.37	QP
4	287.99	23.44	1.05	12.83	37.32	47.00	-9.68	QP
5	614.21	11.11	1.48	18.50	31.09	47.00	-15.91	QP
6	830.40	18.36	1.67	20.37	40.40	47.00	-6.60	QP


Note: 1. All readings are Quasi-peak values.
2. Measured= Reading + Antenna Factor + Cable Loss
3. The emission that are 20db below the official limit are not reported

Model No.	BM01	Test Mode	TM1
Environmental Conditions	23.8°C, 54.1% RH	Distance	3m
Test Engineer	Scent Hu		

Frequency MHz	Emission Level dB μ V/m		Limits dB μ V/m		Margin dB μ V/m		Polarization
	Peak	AV	Peak	AV	Peak	AV	
1307.73	51.35	39.35	70.00	50.00	-18.65	-10.65	H
1954.72	56.20	33.39	70.00	50.00	-13.80	-16.61	H
2116.99	48.07	38.71	70.00	50.00	-21.93	-11.29	H
3228.33	48.47	34.34	74.00	54.00	-25.53	-19.66	H
4489.05	54.82	30.31	74.00	54.00	-19.18	-23.69	H
5870.43	48.38	31.69	74.00	54.00	-25.62	-22.31	H
1305.48	50.34	38.06	70.00	50.00	-19.66	-11.94	V
1958.34	56.13	32.50	70.00	50.00	-13.87	-17.50	V
2113.58	48.54	39.72	70.00	50.00	-21.46	-10.28	V
3229.14	48.04	35.34	74.00	54.00	-25.96	-18.66	V
4486.33	55.03	29.03	74.00	54.00	-18.97	-24.97	V
5870.70	49.39	30.82	74.00	54.00	-24.61	-23.18	V

5. HARMONIC CURRENT EMISSIONS

5.1. Test Configuration



5.2. Test Standard

According to EN 301 489-1 V2.1.1(2017-02) & EN 61000-3-2: 2014

5.3. Test Data

N/A

Note: Because power of EUT less than 75W, According standard EN 61000-3-2, Harmonic current unnecessary to test.

Note: All test modes were performed, but only the worst data was recorded.

7. GENERAL PERFORMANCE CRITERIA FOR IMMUNITY TEST

7.1. Performance criteria for Continuous phenomena applied to Transmitter (CT)

For equipment of type II or type III that requires a communication link that is maintained during the test, it shall be verified by appropriate means supplied by the manufacturer that the communication link is maintained during each individual exposure in the test sequence.

Where the EUT is a transmitter, tests shall be repeated with the EUT in standby mode to ensure that any unintentional transmission does not occur.

7.2. Performance criteria for Transient phenomena applied to Transmitter (TT)

For equipment of type II or type III that requires a communication link that is maintained during the test, this shall be verified by appropriate means supplied by the manufacturer during each individual exposure in the test sequence. Where the EUT is a transmitter, tests shall be repeated with the EUT in standby mode to ensure that any unintentional transmission does not occur.

7.3. Performance criteria for Continuous phenomena applied to Receiver (CR)

For equipment of type II or type III that requires a communication link that is maintained during the test, it shall be verified by appropriate means supplied by the manufacturer that the communication link is maintained during each individual exposure in the test sequence. Where the EUT is a transceiver, under no circumstances shall the transmitter operate unintentionally during the test.

7.4. Performance criteria for Transient phenomena applied to Receiver (TR)

For equipment of type II or type III that requires a communication link that is maintained during the test, this shall be verified by appropriate means supplied by the manufacturer during each individual exposure in the test sequence. Where the EUT is a transceiver, under no circumstances shall the transmitter operate unintentionally during the test.

Performance criteria for ETSI EN 301 489-17 V3.1.1(2017-02)


Criteria	During test	After test
A	Shall operate as intended. May show degradation of performance(see note 1). Shall be no loss of function. Shall be no unintentional transmissions.	Shall operate as intended. Shall be no degradation of performance (see note 2). Shall be no loss of function. Shall be no loss of stored data or user programmable functions.
B	May show loss of function (one or more). May show degradation of performance(see note 1). No unintentional transmissions.	Functions shall be self-recoverable. Shall operate as intended after recovering. Shall be no degradation of performance (see note 2). Shall be no loss of stored data or user programmable functions.
C	May be loss of function (one or more).	Functions shall be recoverable by the operator. Shall operate as intended after recovering. Shall be no degradation of performance (see note 2).

NOTE 1: Degradation of performance during the test is understood as a degradation to a level not below a minimum performance level specified by the manufacturer for the use of the apparatus as intended. In some cases the specified minimum performance level may be replaced by a permissible degradation of performance. If the minimum performance level or the permissible performance degradation is not specified by the manufacturer then either of these may be derived from the product description and documentation (including leaflets and advertising) and what the user may reasonably expect from the apparatus if used as intended.

NOTE 2: No degradation of performance after the test is understood as no degradation below a minimum performance level specified by the manufacturer for the use of the apparatus as intended. In some cases the specified minimum performance level may be replaced by a permissible degradation of performance. After the test no change of actual operating data or user retrievable data is allowed. If the minimum performance level or the permissible performance degradation is not specified by the manufacturer then either of these may be derived from the product description and documentation (including leaflets and advertising) and what the user may reasonably expect from the apparatus if used as intended.

8. RF ELECTROMAGNETIC FIELD (80 MHZ–6000 MHZ)

8.1. Test Configuration



8.2. Test Standard

ETSI 301 489-1, EN 301 489-17
(EN 61000-4-3: 2006+A2: 2010)

Test level 2 at 3V / m.

8.3. Severity Level

Level	Field Strength V/m
1.	1
2.	3
3.	10
X	Special

Performance criterion: A

8.4. Test Procedure

The EUT and its simulators are placed on a turn table which is 0.8 meter above ground. EUT is set 3 meter away from the transmitting antenna which is mounted on an antenna tower. Both horizontal and vertical polarization of the antenna are set on test. Each of the four sides of EUT must be faced this transmitting antenna and measured individually. In order to judge the EUT performance, a CCD camera is used to monitor EUT screen. All the scanning conditions are as follows:

Condition of Test	Remarks
1. Fielded Strength	3 V/m (Severity Level 2)
2. Radiated Signal	Unmodulated
3. Scanning Frequency	80 – 6000 MHz
4. Dwell time of radiated	0.0015 decade/s
5. Waiting Time	3 Sec.

8.5. Test Result

RF ELECTROMAGNETIC FIELD			
Standard	☐ IEC 61000-4-3 ☒ EN 61000-4-3		
Applicant	SAGE HUMAN ELECTRONICS INTERNATIONAL CO.,LTD		
EUT	Bluetooth Speaker	Temperature	23.8℃
M/N	BM01	Humidity	54.1 %
Test Mode	TM1-TM5	Criterion	B
Test Engineer	Scent Hu		

BT Test Result:

EUT Working Mode	Antenna Polarity	Frequency (MHz)	Field Strength (V/m)	Observation	Position	Conclusion
Operating Mode	Vertical	80--6000	3	CT,CR	Front, Right, Left, Back	Pass
	Horizontal	80--6000	3	CT,CR	Front, Right, Left, Back	Pass
Idle	Vertical	80--6000	3	See Note	Front, Right, Left, Back	Pass
	Horizontal	80--6000	3	See Note	Front, Right, Left, Back	Pass

TM2-TM5 Test Result:


EUT Working Mode	Antenna Polarity	Frequency (MHz)	Field Strength (V/m)	Observation	Position	Conclusion
Operating Mode	Vertical	80--6000	3	See Note	Front, Right, Left, Back	Pass
	Horizontal	80--6000	3	See Note	Front, Right, Left, Back	Pass
Idle	Vertical	80--6000	3	See Note	Front, Right, Left, Back	Pass
	Horizontal	80--6000	3	See Note	Front, Right, Left, Back	Pass

***Note: Unintentional transmission is not founded from the EUT.

9. ELECTROSTATIC DISCHARGE

Please refer to ETSI EN 301 489-1 and EN 61000-4-2.

9.1. Test Configuration



EN 61000-4-2 specifies that a tabletop EUT shall be placed on a non-conducting table which is 80 centimeters above a ground reference plane and that floor mounted equipment shall be placed on a insulating support approximately 10 centimeters above a ground plane. During the tests, the EUT is positioned over a ground reference plane in conformance with this requirement.

For tabletop equipment, a 1.5 by 1.0-meter metal sheet (HCP) is placed on the table and connected to the ground plane via a metal strap with two 470 k Ohms resistors in series. The EUT and attached cables are isolated from this metal sheet by 0.5-millimeter thick insulating material. A Vertical Coupling Plane (VCP) grounded on the ground plane through the same configuration as in the HCP is used.

9.2. Test Procedure

ETSI EN 301 489-1 V2.1.1 (2017-02)/ EN 61000-4-2: 2009

Test level 3 for Air Discharge at ± 8 kV

Test level 2 for Contact Discharge at ± 4 kV

9.2.1. Air Discharge

This test is done on a non-conductive surface. The round discharge tip of the discharge electrode shall be approached as fast as possible to touch the EUT. After each discharge, the discharge electrode shall be removed from the EUT. The generator is then re-triggered for a new single discharge and repeated 10 times for each pre-selected test point. This procedure shall be repeated until all the air discharge completed.

9.2.2. Contact Discharge

All the procedure shall be same as Section 9.2.1. except that the tip of the discharge electrode shall touch the EUT before the discharge switch is operated.

9.2.3. Indirect Discharge For Horizontal Coupling Plane

At least 10 single discharges (in the most sensitive polarity) shall be applied at the front edge of each HCP opposite the center point of each unit (if applicable) of the EUT and 0.1m from the front of the EUT. The long axis of the discharge electrode shall be in the plane of the HCP and perpendicular to its front edge during the discharge.

9.2.4. Indirect Discharge For Vertical Coupling Plane

At least 10 single discharges (in the most sensitive polarity) shall be applied to the center of one vertical edge of the coupling plane. The coupling plane, of dimensions 0.5m X 0.5m, is placed parallel to, and positioned at a distance of 0.1m from the EUT. Discharges shall be applied to the coupling plane, with this plane in sufficient different positions that the four faces of the EUT are completely illuminated.

9.3. Test Data

PASS.

Electrostatic Discharge Test Results

Standard	☐ IEC 61000-4-2 ☒ EN 61000-4-2		
Applicant	SAGE HUMAN ELECTRONICS INTERNATIONAL CO.,LTD		
EUT	Bluetooth Speaker	Temperature	23.8℃
M/N	BM01	Humidity	54.1%
Criterion	B	Pressure	1021mbar
Test Mode	TM1-TM5	Test Engineer	Scent Hu

TEST RESULT OF BT

Test Voltage	Coupling	Observation	Result (Pass/Fail)
±2KV, ±4kV	Contact Discharge	TT, TR	Pass
±2KV, ±4kV, ±8kV	Air Discharge	TT, TR	Pass
±2KV, ±4kV	Indirect Discharge HCP	TT, TR	Pass
±2KV, ±4kV	Indirect Discharge VCP	TT, TR	Pass


TEST RESULT OF TM2-TM5

Test Voltage	Coupling	Result (Pass/Fail)
±2KV, ±4kV	Contact Discharge	Pass
±2KV, ±4kV, ±8kV	Air Discharge	Pass
±2KV, ±4kV	Indirect Discharge HCP	Pass
±2KV, ±4kV	Indirect Discharge VCP	Pass

Note: The EUT performance complied with performance criteria for CT&CR to MS Function and there is no any degradation of performance and function.

10. ELECTRICAL FAST TRANSIENT IMMUNITY

10.1. Test Configuration



10.2. Test Standard

EN 301 489-1 V2.1.1/ EN61000-4-4: 2012

Test level 2 at 1 kV

Test level

Level	Open Circuit Output Test Voltage $\pm 10\%$	
	On Power Supply Lines	On I/O (Input/Output) Signal data and control lines
1	0.5 kV	0.25 kV
2	1 kV	0.5 kV
3	2 kV	1 kV
4	4 kV	2 kV
X	Special	Special

Performance criterion: B

10.3. Test Procedure

The EUT is put on the table, which is 0.8 meter high above the ground. This reference ground plane shall project beyond the EUT by at least 0.1m on all sides and the minimum distance between EUT and all other conductive structure, except the ground plane beneath the EUT, shall be more than 0.5m.

10.4.1. For input and output AC power ports:

The EUT is connected to the power mains by using a coupling device, which couples the EFT interference signal to AC power lines. Both polarities of the test voltage should be applied during compliance test and the duration of the test is 2 minutes.

10.4.2. For signal lines and control lines ports: No I/O ports. It's unnecessary to test.

10.4.3. For DC output line ports: It's unnecessary to test.

10.4. Test Data

PASS.

Please refer to the following page.

Electrical Fast Transient/Burst Test Results

Standard	☐ IEC 61000-4-4 ☒ EN 61000-4-4		
Applicant	SAGE HUMAN ELECTRONICS INTERNATIONAL CO.,LTD		
EUT	Bluetooth Speaker	Temperature	24.6℃
M/N	BM01	Humidity	53.1%
Test Mode	TM1-TM5	Criterion	B
Test Engineer	Scent Hu		

TEST RESULT OF BT


Line	Test Voltage	Polarity	Observation	Result (Pass/Fail)
L	1KV	+/-	TT, TR	Pass
N	1KV	+/-	TT, TR	Pass
L-N	1KV	+/-	TT, TR	Pass

TEST RESULT OF TM2-TM5

Line	Test Voltage	Polarity	Result (Pass/Fail)
L	1KV	+/-	Pass
N	1KV	+/-	Pass
L-N	1KV	+/-	Pass

11. RF COMMON MODE

11.1. Test Configuration



11.2. Test Standard

EN 301 489-1 V2.1.1/ EN 61000-4-6: 2014
 Test level 2 at 3 V (r.m.s.), 0.15 MHz ~ 80 MHz,
 Modulation type: AM
 Modulation depth: 80%
 Modulation signal: 1 kHz

Test level

Level	Voltage Level (r.m.s.) (V)
1	1
2	3
3	10
X	Special

Performance criterion: A

11.3. Test Procedure

11.3.1. Let the EUT work in test mode and test it.

11.3.2. The EUT are placed on an insulating support 0.1 m high above a ground reference plane. CDN (coupling and decoupling device) is placed on the ground plane about 0.3 m from EUT. Cables between CDN and EUT are as short as possible, and their height above the ground reference plane shall be between 30 and 50 mm (where possible).

11.3.3. The disturbance signal described below is injected to EUT through CDN.

11.3.4. The EUT operates within its operational mode(s) under intended climatic conditions after power on.

11.3.5. The frequency range is swept from 150 kHz to 80 MHz using 3V signal level, and with the disturbance signal 80% amplitude modulated with a 1kHz sine wave.

11.3.6. The rate of sweep shall not exceed 1.5×10^{-3} decades/s. Where the frequency is swept incrementally, the step size shall not exceed 1% of the start and thereafter 1% of the preceding frequency value.

11.3.7. Recording the EUT operating situation during compliance testing and decide the EUT immunity criterion.

11.4. Test Data

PASS.

Please refer to the following page.

Injected Currents Susceptibility Test Results

Standard	☐ IEC 61000-4-6 ☒ EN 61000-4-6		
Applicant	SAGE HUMAN ELECTRONICS INTERNATIONAL CO.,LTD		
EUT	Bluetooth Speaker	Temperature	24.6℃
M/N	BM01	Humidity	53.6%
Test Mode	TM1-TM5	Criterion	A
Test Engineer	Scent Hu		

TEST RESULT OF BT

Frequency Range (MHz)	Strength (Unmodulated)	Injected Position	Observation	Result (Pass/Fail)
0.15 ~ 10	3V	AC Mains	CT, CR	Pass
10 ~ 30	3V to 1V			
30 ~ 80	1V			

TEST RESULT OF TM2-TM5

Frequency Range (MHz)	Strength (Unmodulated)	Injected Position	Result (Pass/Fail)
0.15 ~ 10	3V	AC Mains	Pass
10 ~ 30	3V to 1V		
30 ~ 80	1V		

Remark:

1. Modulation Signal:1kHz 80% AM

2. Measurement Equipment :


Simulator: CIT-10 (FRANKONIA)

CDN : ☒CDN-M2 (FRANKONIA)

☐CDN-M3 (FRANKONIA)

12. SURGES, LINE TO LINE AND LINE TO GROUND

12.1. Test Configuration



12.2. Test Standard

ETSI EN 301 489-1 V2.1.1 / EN 61000-4-5: 2014

L-N: Test level 2 at 1 kV

L-PE, N-PE Test Level 3 at 2kV

Test Level

Open Circuit Output Test Voltage $\pm 10\%$		
Level	On Power Supply Lines	On I/O (Input/Output) Signal data and control lines
1	0.5 kV	0.25 kV
2	1 kV	0.5 kV
3	2 kV	1 kV
4	4 kV	2 kV
X	Special	Special

Performance criterion: B

12.3. Test Procedure

- 12.3.1. For line to line coupling mode, provide a 0.5 kV 1.2/50us voltage surge (at open-circuit condition).
- 12.3.2. At least 5 positive and 5 negative (polarity) tests with a maximum 1/min repetition rate are conducted during test.
- 12.3.3. Different phase angles are done individually.
- 12.3.4. Record the EUT operating situation during compliance test and decide the EUT immunity criterion for above each test.

12.4. Test Data

Surge Immunity Test Result			
Standard	☐ IEC 61000-4-5 ☒ EN 61000-4-5		
Applicant	SAGE HUMAN ELECTRONICS INTERNATIONAL CO.,LTD		
EUT	Bluetooth Speaker	Temperature	24.6℃
M/N	BM01	Humidity	53.1%
Test Mode	TM1-TM5	Criterion	A
Test Engineer	Scent Hu		

TEST RESULT OF BT


Location	Polarity	Phase Angle	Number of Pulse	Pulse Voltage (KV)	Observation	Result (Pass/Fail)
L-N	+	0°, 90°, 180°, 270°	5	1.0	TT, TR	Pass
	-	0°, 90°, 180°, 270°	5	1.0	TT, TR	Pass

TEST RESULT OF TM2-TM5

Location	Polarity	Phase Angle	Number of Pulse	Pulse Voltage (KV)	Result (Pass/Fail)
L-N	+	0°, 90°, 180°, 270°	5	1.0	Pass
	-	0°, 90°, 180°, 270°	5	1.0	Pass

13. VOLTAGE DIPS/INTERRUPTIONS IMMUNITY TEST

13.1. Test Configuration



13.2. Test Standard

ETSI EN 301 489-1 V2.1.1/ EN 61000-4-11: 2004
Test levels and Performance Criterion

Test Level

Voltage Reduction %U _T	Voltage dips %U _T	Duration (in period)
100	0	0.5
100	0	1
30	70	5
Voltage Reduction %U _T	Voltage Interruptions %U _T	Duration (in period)
100	0	250

Performance criterion: B&C

13.3. Test Procedure

13.3.1. The interruption is introduced at selected phase angles with specified duration.

13.3.2. Record any degradation of performance.

13.4. Test Data

Voltage Dips And Interruptions Test Results			
Standard	☐ IEC 61000-4-11 ☒ EN 61000-4-11		
Applicant	SAGE HUMAN ELECTRONICS INTERNATIONAL CO.,LTD		
EUT	Bluetooth Speaker	Temperature	24.6℃
M/N	BM01	Humidity	53.1%
Test Mode	TM1-TM5	Criterion	A
Test Engineer	Scent Hu		

TEST RESULT OF BT				
Test Level % U _T	Voltage Dips & Short Interruptions % U _T	Duration (in periods)	Observation	Result (Pass/Fail)
0	100	0.5P	TT, TR	Pass
0	100	1P	TT, TR	Pass
70	30	25P	TT, TR	Pass
0	100	250P	TT, TR	Pass

TEST RESULT OF TM2-TM5			
Test Level % U _T	Voltage Dips & Short Interruptions % U _T	Duration (in periods)	Result (Pass/Fail)
0	100	0.5P	Pass
0	100	1P	Pass
70	30	25P	Pass
0	100	250P	Pass

14. LIST OF MEASURING EQUIPMENT

LINE CONDUCTED EMISSION

Item	Equipment	Manufacturer	Model No.	Serial No.	Cal Date	Due Date
1	EMI Test Software	AUDIX	E3	/	N/A	N/A
2	EMI Test Receiver	R&S	ESPI	101840	2019-06-11	2020-06-10
3	Artificial Mains	R&S	ENV216	101288	2019-06-12	2020-06-11
4	10dB Attenuator	SCHWARZBEC K	MTS-IMP-136	261115-001-0032	2019-06-11	2020-06-10
5	Impedance Stabilization Network	TESEQ	ISN T800	45130	2018-11-15	2019-11-14

RADIATED DISTURBANCE

Item	Equipment	Manufacturer	Model No.	Serial No.	Cal Date	Due Date
1	EMI Test Software	AUDIX	E3	/	N/A	N/A
2	3m Semi Anechoic Chamber	SIDT FRANKONIA	SAC-3M	03CH03-HY	2019-06-12	2020-06-11
3	Positioning Controller	MF	MF-7082	/	2019-06-12	2020-06-11
4	By-log Antenna	SCHWARZBEC K	VULB9163	9163-470	2018-07-26	2019-07-25
5	Horn Antenna	SCHWARZBEC K	BBHA 9120D	9120D-1925	2018-07-02	2019-07-01
6	EMI Test Receiver	R&S	ESR 7	101181	2019-06-12	2020-06-11
7	RS SPECTRUM ANALYZER	R&S	FSP40	100503	2018-11-15	2019-11-14
8	AMPLIFIER	QuieTek	QTK	CHM/0809065	2018-11-15	2019-11-14
9	RF Cable-R03m	Jye Bao	RG142	CB021	2019-06-12	2020-06-11
10	RF Cable-HIGH	SUHNER	SUCOFLEX 106	03CH03-HY	2019-06-12	2020-06-11

VOLTAGE FLUCTUATION AND FLICKER/HARMONIC CURRENT EMISSIONS

Item	Equipment	Manufacturer	Model No.	Serial No.	Cal Date	Due Date
1	Power Analyzer Test System	Voltech	PM6000	200006700523	2019-06-12	2020-06-11

RF ELECTROMAGNETIC FIELD

Item	Equipment	Manufacturer	Model No.	Serial No.	Cal Date	Due Date
1	RS Test Software	Tonscend	/	/	N/A	N/A
2	ESG Vector Signal Generator	Agilent	E4438C	MY42081396	2018-11-15	2019-11-14
3	3m Semi Anechoic Chamber	SIDT FRANKONIA	SAC-3M	03CH03-HY	2019-06-12	2020-06-11
4	RF POWER AMPLIFIER	OPHIR	5225R	1052	NCR	NCR
5	RF POWER AMPLIFIER	OPHIR	5273F	1019	NCR	NCR
6	Stacked Broadband Log Periodic Antenna	SCHWARZBEC K	STLP 9128	9128ES-145	NCR	NCR
7	Stacked Mikrowellen Log.-Per Antenna	SCHWARZBEC K	STLP 9149	9149-484	NCR	NCR
8	Electric field probe	Narda S.TS./PMM	EP601	611WX80208	2019-03-25	2020-03-24

ELECTROSTATIC DISCHARGE

Item	Equipment	Manufacturer	Model No.	Serial No.	Cal Date	Due Date
1	ESD Simulator	SCHLODER	SESD 230	604035	2019-06-13	2020-06-12

ELECTRICAL FAST TRANSIENT IMMUNITY

Item	Equipment	Manufacturer	Model No.	Serial No.	Cal Date	Due Date
1	Immunity Simulative Generator	EM TEST	UCS500 M4	0101-34	2019-06-11	2020-06-10

RF COMMON MODE

Item	Equipment	Manufacturer	Model No.	Serial No.	Cal Date	Due Date
1	Simulator	FRANKONIA	CIT-10/75	A126A1195	2019-06-11	2020-06-10
2	CDN	FRANKONIA	CDN-M2+M3	A2210177	2019-06-11	2020-06-10
3	6dB Attenuator	FRANKONIA	DAM25W	1172040	2019-06-11	2020-06-10

SURGES, LINE TO LINE AND LINE TO GROUND

Item	Equipment	Manufacturer	Model No.	Serial No.	Cal Date	Due Date
1	Immunity Simulative Generator	EM TEST	UCS500 M4	0101-34	2019-06-11	2020-06-10

VOLTAGE DIPS/INTERRUPTIONS IMMUNITY TEST

Item	Equipment	Manufacturer	Model No.	Serial No.	Cal Date	Due Date
1	Voltage dips and up generator	3CTEST	VDG-1105G	EC0171014	2019-06-11	2020-06-10


Note: All equipment is calibrated through CHINA CEPREI LABORATORY and GUANGZHOU LISAI CALIBRATION AND TEST CO., LTD.

15.TEST SETUP PHOTOGRAPHS

15.1.Photo of Radiated Emissions Measurement



Below 1G



Above 1G

15.2.Photo of Power Line Conducted Emissions Measurement




15.3.Photo of Harmonic & Flicker Measurement



15.4.Photo of Electrostatic Discharge Test



15.5.Photo of Radio-frequency, Continuous radiated disturbance



15.6.Photo of Electrical Fast Transient/Burst& Surge Immunity Test



15.7.Photo of Injected Currents Susceptibility Test



15.8 Photo of Voltage Dips and Short Interruptions Immunity Test



16.EXTERNAL AND INTERNAL PHOTOS OF THE EUT




Fig. 1



Fig. 2



Fig. 3



Fig. 4




Fig. 5




Fig. 6




Fig. 7



Fig. 8




Fig. 9




Fig. 10




Fig. 11




Fig. 12

-----THE END OF REPORT-----