



DATA SHEET

High-density storage engineered for the data demands of tomorrow.

Exos 4U74 and 4U100

Exos 4U74 and 4U100 are the most comprehensive storage solutions for tomorrow's data demands. Engineered by Seagate, these ultra-dense SAS-4 JBOD systems combine next-gen Mozaic drive readiness with energy-efficient design for AI, edge and sovereign data infrastructure.



Built for:

- Data consolidation and infrastructure refresh
- Hybrid cloud repatriation and tiered storage
- Edge aggregation and compliance-driven deployments
- Managed service scaling and modular expansion

Key Advantages

Industry-leading capacity 3.2 PB in a single enclosure, engineered by Seagate. Built to accommodate today's largest drives and tomorrow's innovations.

Customisable & configurable Support for deployment of either SAS or SATA drives. Pre-configured SAS zoning for streamlined deployment.

Operational efficiency Up to 30% lower power consumption and 70% improved cooling efficiency compared to previous generations. Optimised airflow and best-in-class watts-per-terabyte performance. Designed to reduce OpEx and minimise TCO.

Simplified deployment Enclosure options for 1 m and 1.2 m rack depth. Built-in carrier and internal cable management. Toolless access and drawer-style serviceability. Built for flexibility across OCP racks, standard data centres and edge deployments. Configurable for diverse workload requirements.

Enterprise-grade security Seagate Secure™ component certificate. In-band via SES/out-of-band management via Redfish. Compliance-ready for air-gapped and sovereign data deployments.



Specifications	Up to 3.2PB
Chassis Specifications	
Operation	High Availability (SAS), Non-High Availability (SATA or SAS)
Host Interface - I/O Ports	Dual redundant I/O Modules (IOM) 4x Mini-SAS HD port per IOM (24 Gb/s, 12 Gb/s, 6 Gb/s SAS speeds supported)
Management/Status Reporting	SCSI enclosure services (in-band) Redfish API, SSH CLI (out of band via Ethernet)
Drive Interface	12 Gb/s SAS 6Gb/s SATA 24 Gbps SAS SSDs
Max Drives per Enclosure	100 x 3.5in drive bays 74 x 3.5in drive bays up to 26 SSD for a full list of supported drives, please contact your account or sales manager
LED Indicators	Front: System Power, Host connectivity, System ID, Fault-drawer, Fault Application, Fault-Rear panel Rear: IOM (Power, Fault, mini-SAS-HD Port activity, mini-SAS-HD Port Fault) RJ45 (Speed, Activity) Fan (Fault) PSU(Power, Fault) Drive: ID, Fault Expander Module LED: Expander Power, Fault
Physical Dimensions and Weight	<div> 4U100 Height: 175.5 mm/6.91 in Width: 448.5 mm/17.66 in Depth: 1146.0 mm/45.12 in Weight (without drives): 59.9 kg / 132 lbs Weight (with drives): 125.6 kg/277 lbs </div> <div> 4U74 Height: 175.5 mm/6.91 in Width: 448.5 mm/17.66 in Depth: 932.0 mm/36.69 in Weight (without drives): 49.9 kg / 110 lbs Weight (with drives): 98.9 kg / 218 lbs </div>
Serviceability	Hot swappable components: Drives (HDD/SSD), IOM, power supply units (PSU), fans, link expansion modules (LEM) Cable Management (CMA): No external cable management required
Cooling	
Enclosure	4 dual-impeller enclosure fans, front-to-rear cooling
Power Supply	Dual PSUs with built-in fans
Power Requirements	
Input Power Requirements	200-240VAC, 50Hz/60Hz
Max Power Output per PSU	1800W
Power Supply Units	2x Ecodesign 1800W PSU Model No. CSU1800AT-3 Power Efficiency: 80+ Titanium Power Factor Correction (PFC): ≥ 0.95 for 20% loading or above 2x Ecodesign 1800W PSU Model No. TEC1800-12-074NA Power Efficiency: 80+ Titanium Power Factor Correction (PFC): ≥ 0.95 for 20% loading or above
Environmental Requirements	
Operating/Non-operating Altitude	–100 m to 3,000 m (–330 ft to 10,000 ft) / –100 m to 12,192 m (–330 ft to 40,000 ft)
Operating/Non-operating Temperature	ASHRAE A2, 10°C to 35°C (50°F to 95°F), derate 1°C per 300m above 900m, 20°C/hr max rate of change / –40°C to 70°C (–40°F to 158°F) ASHRAE A3 under certain conditions ¹
Operating/Non-operating Humidity	–12°C DP min and 8% RH to 21°C DP max and 80% RH / 5% RH to 100% RH (non condensing) and max 29°C DP
Operating/Non-operating Shock ²	5 Gs, half sine, 11ms / X/Y axis: +/- 12Gs, half sine, 11ms; Z-axis: 20Gs, half sine, 7ms
Operating/Non-operating Vibration ³	Random Vibration - 0.18gRMS, 10-500Hz, 30 min each axis / Random Vibration - Z-axis - 0.78gRMS, 5-200Hz, 30 mins; X/Y-axis - 0.25gRMS, 5-200Hz, 30 mins each
Sound Power	Sound Power <78 dBA at 27C ambient and nominal HDD workload. (NEBS)/Sound Pressure <85 dBA at 23C ambient and nominal HDD workload. (OSHA)
Standards/Approvals	
Safety Certifications	UL 62368-1 (United States) CAN/CSA-C22.2 No. 62368-1:19 (Canada) EN 62368-1 (European Union) IEC 62368-1 (International) CCC (China PRC – CCC Power Supplies) BIS (India – BIS Power Supplies)
Ecodesign	Commission Regulation (EU) 2019/424 (Directive 2009/125/EC)
Emissions (EMC)	FCC CFR 47 Part 15 Subpart B Class A (United States) ICES/NMB-003 Class A (Canada) EN 55032 Class A, EN 61000-3-2, EN 61000-3-3 (Europe) AS/NZS CISPR 32 Class A (Australia/New Zealand) VCCI Class A (Japan) KN 32 Class A CNS 13438 Class A (Taiwan)
Immunity	EN 55024 (EU) KN 24/KN 35 (S. Korea) CISPR 24/CISPR35
Environmental Standards ⁴	EU RoHS Directive (2011/65/EU) EU WEEE Directive (2012/19/EU) EU REACH Regulation (EC) No 1907/2006 EU WFD (2008/98/EC) EU POPs Regulation (EU) 2019/1021
Standard Marks/Approvals	Australia/New Zealand (RCM), Canada (cUL/ICES/NMB-003 Class A), China (CCC – PSU only), European Union (CE), Japan (VCCI), South Korea (KC), Taiwan (BSMI), United States (FCC/UL)
Country Approvals	Australia/New Zealand (RCM), Canada (cUL/ICES/NMB-003 Class A), China (CCC – PSU only), European Union (CE), Germany (GS), Japan (VCCI), South Korea (KC), Taiwan (BSMI), United States (FCC/UL), The Eurasian Economic Union (EAC), India (BIS)

1 ASHRAE A3 compliant, 5°C to 40°C, drate 1°C per 175 m above 900 m, <=9W per drive power consumptions (extreme conditions), with all fan units functional, for current and future HDD generations upto (including) Mozaic 4+.

2 Operating: 10 shocks in +/- X,Y axis, 10 shocks in +Z - 50 total shocks/Nonoperating Shock: 6 shocks in +/- XY axis (24 total shocks), 2 shocks Z-axis

3 Operating: Sine Sweep - Z-axis - 0.17g, 5-50Hz, 1 octave/minute, 25 up and 25 down; X/Y-axis - 0.12g, 5-50Hz, 1 octave/minute, 25 up and 25 down/
Non-operating Sine Sweep - Z-axis - 0.6g, 5-50Hz, 1 octave/minute, 25 up and 25 down; X/Y-axis - 0.3g, 5-50Hz, 1 octave/minute, 25 up and 25 down (Sine sweep are not pass/fail criteria and is used for engineering purposes.

4 For the full list of environmental standards, please contact your account manager or sales representative.

seagate.com



© 2025 Seagate Technology LLC. All rights reserved. Seagate, Seagate Technology, and the Spiral logo are registered trademarks of Seagate Technology LLC in the United States and/or other countries. Exos is either a trademark or registered trademark of Seagate Technology LLC or one of its affiliated companies in the United States and/or other countries. All other trademarks or registered trademarks are the property of their respective owners. When referring to drive capacity, one gigabyte, or GB, equals one billion bytes and one terabyte, or TB, equals one trillion bytes. Your computer's operating system may use a different standard of measurement and report a lower capacity. In addition, some of the listed capacity is used for formatting and other functions, and thus will not be available for data storage. Seagate reserves the right to change, without notice, product offerings or specifications. SC111.1-2510US